

CP2500 Series

Low Profile Common Point Ground

Description

Transforming Technologies CP2500 low profile ground cord offers the common ground point required by ANSI/ESD S-6.1 and ANSI/ESD-S20.20.

The low profile common point ground includes a 15' long black PVC cord made with 7 strand tinsel wire to #10 ring terminal. Dual standard banana jacks allow two workers the ability to plug into onto one ground point. The molded connection point houses a 1 meg Ohm 1/4 watt resistor and attaches to table mats via 10mm stud.

Meets or exceeds requirements of ANSI ESD-S20.20 and ANSI/ESD S-6.1



Product Specifications

Cord Length:	15'
Ground Terminal:	#10 ring type
Wire Insulation:	PU/PVC
Resistor:	1 Meg ohm
Color:	Black

Product Numbers

<u>Item Number</u>	<u>Description</u>
CP2522	Low Profile CPG, 15' cord, 10mm Male, 1 meg
CP2524	Low Profile CPG, 15' cord, 10mm Female, 1meg
CP2522NR	Low Profile CPG, 15' cord, 10mm Male, No resistor

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.



Transforming Technologies, LLC

3719 King Road.
Toledo, OH 43617

Phone: 1.419.841.9552
Fax: 1.419.841.3241
www.transforming-technologies.com

Outstanding Alternatives in Static Control